

FRONT LOAD HOT AIR DRYERS



Front Load drying systems feature vertical air flow. Air enters at the top of the drying chamber and flows downward, exiting through the grating on the side wall at the bottom of the chamber. These systems are designed to dry racks or parts that are taller than 24", and those that would dry quicker with downward air flow. Hanger rods and a work rest are standard. Side wall brackets, designed to accept multiple shallow trays, are optional-ly available. These models are available with vertical sliding doors, horizontal sliding doors, or hinged double doors. The vertical door models have a wider chamber, while the horizontal door models are available with taller chambers.

Front Load Horizontal Door Style – Standard Models

Model #	Internal Dimensions (L-R) x (F-B) x H	Overall Dimensions	Power Requirements	
			Electrically Heated	Steam Heated
FLH3025	25" x 30" x 30"	64" x 37" x 96"	230V/3PH-25A	120V/1PH-15A
FLH4825	25" x 30" x 45"	64" x 37" x 96"	230V/3PH-25A	120V/1PH-15A
FLH6025	25" x 30" x 57"	64" x 37" x 96"	230V/3PH-35A	120V/1PH-15A
* Overall height can be reduced on these models if preferred				



100 Minnesota Ave., Unit 4
Warwick, RI 02888
401-421-9306