

TOP LOAD HOT AIR DRYERS



Greco Industrial Top Load Dryers are designed for use in industrial applications where production requirements and efficiency are the primary criteria. They offer large work chambers, suitable for high production. As with all Greco dryers, these units offer insulated, double-wall stainless steel construction, a high velocity blower, and in-line radiant heaters. A digital readout temperature control ensures stable temperatures anywhere between ambient and 250 degrees F. All air is circulated within the chamber and reheat-ed, reducing heat-up times and maximizing operating efficiency. These dryers are available with rod-style rack hangers for racked parts, or a removable bottom basket rest for baskets and larger parts.

Model Number	TL3025	TL4825	TL6025
Internal Dimensions	30" x 25" x 30"	45" x 25" x 30"	57" x 25" x 30"
Overall Dimensions	64" x 42" x 41	77" x 42" x 41"	89" x 42" x 41
Power Requirements	230V/3PH-30A or 460V/3PH-15A	230V/3PH-30A or 460V/3PH-15A	230V/3PH-30A or 460V/3PH-15A
Heat Input	7.5 kW	7.5 kW	7.5 kW
Air Flow	1,100 CFM	1,100 CFM	1,100 CFM
Design specifications for standard models are subject to change without notice.			



100 Minnesota Ave., Unit 4
Warwick, RI 02888
401-421-9306

sales@greco-cleaning.com